1.0	Specifications	
1.1	Frequency (GHz)	960Mhz-1216Mhz
1.2	Gain(dB)	7
1.3	Output power	700W(min)
1.4	Power supply	50Volts
1.5	Pulse width	15usec(max)
1.6	Duty Factor	5%
1.7	Output flatness	±0.5db(max,full band)
1.8	RF IN connector	SMA Female
1.9	RF OUT connector	SMA Female
2.0	The power joint form	Pin-count=6pin
		Male pin(male-type pin))
		CON SIP
		Pin-count=2.54+/-0.1mm
2.1	90° PCB connector type	Locking ramp
2.2	Power connector of pin(assignment)	Pin1:BIT, Pin2:GND,Pin3:GND, Pin4:Spare, Pin5:+50V, Pin6:+50V
2.3	RF IN The monitoring signal	
2.4	Name	RF IN DET
2.5	Conector type	Miniature Co-axial Connector male
2.6	Monitoring singnal bit rate	RF OUT-20db to RF OUT-60db
2.7	The monitoring signal gain	±1db
2.8	Monitoring signal of connector adapter	Miniature Co-axial Connector female to SMA female
		Included 4 piece (set)
2.9	Operating temperature	-30° ~+55° （min）
3.0	Storage temperature	-40° ~+65° (min)
3.1	Size	180.5mm×104.3 mm×36.8mm (max)

8F-1, No. 51, Sec. 1, Minsheng E. Rd., Taipei 104 , Taiwan
T:+886-2-2565-2500 F: +886-2-2551-5250 E-mail: sales@temstron.com
2016 Copyright © by TEMSTRON, All Rights Reserved